

**Serie | 6, Wall-mounted cooker hood,
90 cm, Stainless steel
DWB98JQ50B**

A⁺



The wall-mounted chimney hood: Mount it on the wall for complete freedom in your kitchen planning

- **PerfectAir sensor:** automatic control of settings for maximum extractor performance with minimal noise.
- **EcoSilence Drive:** our highly efficient motor saves on energy, not on performance.
- **DirectSelect control:** direct selection of desired settings and light.
- **Extra quiet:** maximum extractor performance with minimal noise.
- **Grease filtration level:** filters out up to 89.6% of the grease from kitchen air.

Technical Data

Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-908/568-1018
Height of product, without chimney (mm) :	46
Net weight (kg) :	19.827
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m ³ /h) :	430
Boost position output recirculating (m ³ /h) :	385.0
Boost position air extraction (m ³ /h) :	843
Number of lights :	3
Noise level (dB(A) re 1 pW) :	55
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable stainless steel
Odour filter :	No
Operating Mode :	Convertible
Delay Shut off modes :	10M
Optional accessories :	
DHZ1223, DHZ1233, DHZ5345, DHZ5346, DSZ5201, DSZ6240, DWZ0XX0I5, DWZ0XX0J5, DWZ1CX1I6, DWZ2CX5C6, DWZ2FX5D1, DZZ0XX0P0, DZZ1XX1B6	
Type of lamps used :	LED
Grease filter type :	Kassette
Connection Rating (W) :	165
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation typology :	Wall-mounted
Material body :	Stainless steel
Approval certificates :	CE, VDE
Plug type :	GB plug
Dimensions of the product, with chimney (if exists) (in) :	/ x x
Dimensions of the packed product (in) :	22.83 x 25.59 x 38.18
Net weight (lbs) :	44
Gross weight (lbs) :	56
Motor location :	Integrated motor in hood chimney
No-return airflow flap :	No
Length electrical supply cord (cm) :	130
Dimensions of the product, with chimney (if exists) (mm) :	614-1064 x 898.0 x 500.0
Dimensions of the packed product (HxWxD) (mm) :	580 x 650 x 970
Net weight (kg) :	19.827
Gross weight (kg) :	25.6



Serie | 6, Wall-mounted cooker hood, 90 cm, Stainless steel DWB98JQ50B

The wall-mounted chimney hood: Mount it on the wall for complete freedom in your kitchen planning

Design

- 90 cm wide
- Box brand design
- Wall mounted hood
- electronic controls via TouchControl with lightline

Performance

- 3 fan speeds setting plus 2 intensive
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 430 m³/h
Intensive 843 m³/h
- Extraction rate in recirculation mode:
Max. normal use: 311 m³/h
Intensive: 385 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13
exhaust air:
Max. normal use: 55 dB(A) re 1 pW (42 dB(A) re 20 µPa sound
pressure)
Intensive: 69 dB(A) re 1 pW (56 dB(A) re 20 µPa sound
pressure)
- Noise levels in recirculation mode:
Max. normal use: 69 dB(A) re 1 pW (56 dB(A) re 20 µPa sound
pressure)
Intensive: 74 dB(A) re 1 pW (61 dB(A) re 20 µPa sound
pressure)

Comfort:

- Automatic intensive revert after 6 min.
- Automatic run on for 10 min.
- Additional noise insulation
- removable metal grease filters
- Easy to clean yes
- air quality sensor 1.1
- Dimmer function
- softLight
- Efficient BLDC-technology
- 3 x 1.5W LED
- 3 removable metal grease filters
- Saturation indicator for metal and charcoal filter
- Energy Efficiency Class: A+
-
- Blower Efficiency Class: A*
- Grease Filtering Efficiency Class: B*

Technical information:

- Suitable for ducted or recirculating operation
- Recirc. kit or clean air kit
- Wall fixing system
- Dimensions exhaust air (HxWxD mm): 628-954 x 898 x 500
- Dimensions recirculating (HxWxD mm): 628-1064 x 898 x 500
- Dimensions recirculating with CleanAir module (HxWxD mm):
689 x 898 x 500 - mounting with outer chimney
809-1139 x 898 x 500 - mounting with telescopic chimney
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Electrical connection rating: 165 W
- Electrical cable length 1.3 m
- Voltage: 220 - 240 V

* In accordance with the EU-Regulation No 65/2014