

## Series 4, Wall-mounted cooker hood, 90 cm, Stainless steel DWBM98G50B





# The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

- LED lighting: For optimal, energy-efficient illumination of your hob
- Ducted or Non-ducted Options
- Absorbs odors with Charcoal Replacement Filters (Available for sale)
- 3-Speed Power Level Options To Suit Your Cooking Style And Recipes

### **Technical Data**

Typology : Wall-mounted

Length electrical supply cord: 180 cm Height of the chimney: 390-780 mm Height of product, without chimney: 60 mm

Net weight: 15.6 kg Type of control: Electronic Number of speed settings: 3

Maximum output air extraction : 800 m³/h Maximum output recirculating air : 650 m³/h

Number of lights : 2 Odour filter : No

Operating Mode : Convertible Total power of the lamps : 3 W Connection Rating : 296 W Voltage : 220-240 V

Frequency: 50 Hz

Plug type : India plug (6 Ampere) Installation typology : Wall-mounted Material body : Stainless steel Plug type : India plug (6 Ampere)

Dimensions of the product, with chimney (if exists) (in) : / x x Dimensions of the packed product : 22.44 x 15.15 x 37.79

Net weight: 34.000 lbs Gross weight: 39.000 lbs

Motor location: Integrated motor in hood chimney

No-return airflow flap : Yes

Length electrical supply cord: 180 cm

Dimensions of the product, with chimney (if exists) : 450-840 x

900.0 x 505.0 mm

Dimensions of the packed product (HxWxD) :  $570 \times 385 \times 960$ 

mm

Net weight : 15.6 kg Gross weight : 17.5 kg





## Series 4, Wall-mounted cooker hood, 90 cm, Stainless steel DWBM98G50B

The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

#### Performance

- Extraction rate according to EN 61591 max. 800 m<sup>3</sup>/h
- 3 speeds

### Design

- Wall mounted hood
- Stainless steel material
- **-** 90 cm wide
- Box design
- TouchControl

#### Comfort

- LED Lighting
- 3 Metal grease filter

### **Tecnical information:**

- Suitable for ducted or recirculating operation
- Dimensions recirculating (HxWxD mm):  $450-840 \times 900 \times 505$
- Electrical cable lenght 1.8 m
- **-** Voltage: 220 240 V
- Plug type: India plug (6 Ampere)



## Series 4, Wall-mounted cooker hood, 90 cm, **Stainless steel** DWBM98G50B





